



Kingwell Fibre

Kingwell Fibre Materials Co.,Ltd

10.2, SANDING SCREEN/ Sand Screen/Abrasive Sand Screen



Application: Sanding surface of woodworking,plaster,metal,plastic,ceramics and removing rusty spots of metal materials,for grinding and polishing treatment.

Performance:

- Open mesh backing reduces loading-save time
- Coated on both sides
- Anti-clogged
- Self-cleaning and last longer
- Reversible use wet or dry
- Flexible for sanding both of contoured and irregular surfaces

SANDING SCREEN grinding & cutting efficiency and durability is far beyond the conventional abrasive materials.

SANDSCREEN can be customized to various rolls, discs, sheets on request.

SANDSCREEN SPEC SHEET



Kingwell Fibre Materials Co.,Ltd

Grain	Silicon Carbide (SIC) Aluminium Oxide (A/O)
Grits	P40-P1000
SANDSCREEN SIZE	
Roll Size	1-1/2"*5yds, 1-1/2"*10yds, 1-1/2"*25yds, 2"* 25yds, 3"* 25yds, 4"* 25yds, 6"* 25yds, 36"*100yds, 36"*300yds
Disc Diameter	13",14",15",16",17",18",19",20",21",22",23",24"
Sheet Size	3-5/16*11",3-2/3*11"(9"),4*5-1/2",4-3/16*11",9*11"
Velcro Size	4",4.5",5",6",7",8",9",10",16"