

### **32, Fibreglass Floor Exhaust Filter for Paint Booth**

Also known as: Fiber glass filter roll, mesh barrier paint, carpet mist, paint arrestor, paint stop



The fiber glass paint arrestor is an environmental filter with green and white color, the density is increased orderly and the bottom density is the largest.

It is able to prevent the short fiber spread, to collect the dissociative particles and to protect the air circulation system and the ceiling filtration systems.

It is mainly used to absorb the over dissociative particles and decrease the pollution.

Purpose :

Specially for sprayed to catch to spray in the paint system of paint fog and stem the dust but design

be applicable to an automobile, furniture, machine zero parts the dry type of etc. spray the paint system and car.



Product characteristic:

- 1 Strong flexibility, the antisplit of the glass fiber filter the material fiber to present to pass to increase structure gradually, catching a rate high
- 2 Can keep shape constant its filtering a fiber have to store paint fog dust.Wear to attach to fix on the material of defend a germ layer
- 3 There is the color noodles to enter spirit noodles for the air, Don't contain silicon ketone
- 4 Prevent fire the Class matches industrial standard DIN4102F1.

Category: plus end with the general type

Material: glass fiber, the windward side is green, outlet side is white

Temperature: 170 °C

Structure: sheets or rolls

The average separation efficiency mist mat: 95%

Characteristics: resistance is low, mist adsorption effect, easy to distinguish between positive and negative, flexible, economical and practical

Applications : spray booth and painting equipment or kitchen trapping system, adsorption of chemical fumes mist systems, and ultimately enable exhaust gases to



## **Kingwell Fibre Materials Co.,Ltd**

meet environmental requirements. Painting room or kitchen smoke emission filter filtering.

Common places: cars, furniture, machinery, hardware and tools, electronic spray paint spray paint room or workshop

Note mist felt: 1: Install mist felt the process, try to wear gloves in contact, so start rolling in fiberglass. 2: mist felt fragile, do not pull hard.

Mist felt technical parameters: (Other sizes could be customized to request)

Specification: 0.8mX14m,1mX20m,2mX20m

Thickness:50mm, 60mm, 100mm